

## A ground-fault protected plug with end seal for Raychem WinterGard heating cables

The H908 120-V Plug-In Power Connection Kit with ground-fault circuit protection simplifies the installation of 120-V WinterGard, Wintergard Plus, and Wintergard Wet electric heating cables for freeze protection of water pipes, refrigeration condensate drain lines, roofs, and gutters.

### The H908 Plug-In Power Connection Kit:

- Enables contractors to simply cut the heating cable to length in the field, install the connection kit, and insert the plug into a standard grounded outlet.
- Powers up to 250 feet of heating cable—up to twice the length that previ-

ous field-assembled plug-in systems could power.

- Provides built-in 27-mA ground-fault protection of equipment as required by national electrical codes.



### General

#### Description

The H908 Kit is a plug-in, ground-fault protected power connecting kit for use with 120-volt heating cables only. The kit includes materials for one power connection and one end seal.

The H908 kit is for use with the following Raychem heating cables and applications.

- WinterGard heating cable for pipes up to 2 inches in diameter in dry areas.
- WinterGard Plus heating cable for pipes up to 6 inches in diameter in dry areas.
- WinterGard Wet heating cable for pipes up to 6 inches in diameter in wet or dry areas and for de-icing roofs, gutters and downspouts.

#### Approvals



718K Pipe Heating Cable  
Also Listed as De-icing and  
Snow Melting Equipment



**Technical Specifications**

The H908 kit contains a plug-in power connection and an end seal for use with 120-volt cut-to-length heating cables. The kit includes a ground-fault equipment protection circuit interrupter (GFEPIC) with a 15 A three-prong plug, plus all the materials and instructions needed to make an end seal and a plug-in power connection.

The 27-mA-rated GFEPIC will trip whenever the fault current to ground is more than 27 mA.

The GFEPIC in the H908 kit will minimize the risk of fire from sustained electrical arcing if the heating cable is improperly installed or damaged during use. The fault currents produced by this arcing may be too small to be stopped by conventional circuit breakers, but the GFEPIC will sense these fault currents and shut off the power.

**Note:** The H908 requires a properly installed electrical ground.

**WinterGard H908 Heating Cable Specifications**

	Heating cable type		
	WinterGard H311	WinterGard Plus H611	WinterGard Wet H612
Service voltage (V)	120	120	120
Maximum circuit length at start-up (ft)			
40°F on pipes	250	150	150
0°F on pipes	150	150	125
Maximum circuit length at start-up (ft)			
32°F on roof and gutter			125
0°F on roof and gutter			100
Circuit breaker rating (A)	15	15	15
Thermal output at 40°F on pipes (W/ft)	3	6	6
Thermal output at 32°F in ice/snow (W/ft)	Do not use in wet areas.	Do not use in wet areas	8
Weight per 100 ft (lb)	6	6	9
Minimum installation temperature (°F)	0	0	0
Maximum exposure temperature (°F)	150	150	150
Environment	Use only in ordinary (nonhazardous) areas. Do not expose to chemicals.		

**Worldwide Headquarters  
Tyco Thermal Controls**

7433 Harwin Drive  
Houston, TX 77036  
USA

Tel: 800-545-6258

Tel: 650-216-1526

Fax: 800-527-5703

Fax: 650-474-7711

info@tycothermal.com

[www.tycothermal.com](http://www.tycothermal.com)

**Canada**

**Tyco Thermal Controls**

250 West St.

Trenton, Ontario

Canada K8V 5S2

Tel: 800-545-6258

Fax: 800-527-5703

**Latin America**

**Tyco Thermal Controls**

7433 Harwin Drive

Houston, TX 77036

United States

Tel: 713-868-4800

Tel: 713-735-8645

Fax: 713-868-2333

**Europe, Middle East, Africa (EMEA)**

**Tyco Thermal Controls**

Romeinse Straat 14

3001 Leuven

België / Belgique

Tel: +32 16 213 511

Fax: +32 16 213 603

**Asia Pacific**

**Tyco Thermal Controls**

20F, Innovation Building,

1009 Yi Shan Rd,

Shanghai 200233,

P.R.China

Tel: +86 21 2412 1688

Fax: +86 21 5426 2937 / 5426 3167

Tyco and other trademarks are the property of Tyco Thermal Controls or its affiliates

**tyco**  

---

**Thermal Controls**

**Important:** All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their particular application. Tyco Thermal Controls makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. Tyco Thermal Controls' only obligations are those in the Tyco Thermal Controls Standard Terms and Conditions of Sale for this product, and in no case will Tyco Thermal Controls or its distributors be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of the product. Specifications are subject to change without notice. In addition, Tyco Thermal Controls reserves the right to make changes—without notification to Buyer—to processing or materials that do not affect compliance with any applicable specification.