

## Application



Special primer for T2Reflecta plates to fix ceramic tiles and natural stones

**T2Reflecta-P-Fix** Primer is a specially formulated primer designed to enable the bonding of adhesive materials to non-porous smooth finishes; Perfect for the installation of ceramic tile or natural stone materials, onto the aluminum surface of T2Reflecta plates.

**T2Reflecta-P-Fix** Primer is a ready to use solvent-free Acrylic based solution which dries as plastic film.

## Technical Data

Material	Special Acrylic based solution
Solvents	none
Colour	Blue
Consistency	liquid
Consumption	150 g/m <sup>2</sup> Sufficient for approx. 30 m <sup>2</sup> T2Reflecta
Mix ratio	Apply undiluted
Dry time when applied	Approx. 1-3 h depending on ambient temperature and applied weight
Working temperature	Min. +5°C Max. +30°C
Density	1,3 kg/l
Temperature exposure	With floor heating max. +50°C
Tool for application	Roller, Brush
Liquid cleaning method	water
Packaging	5 kg bucket

### Storage

- Dry, Cool but frost free
- Shelf life 12 months
- Use contents within a few days once open

### Disposal

- Dispose of using local regulations

## System References

- **T2Reflecta**-Insulation plates (see technical data sheet)
- **T2Reflecta-A-Fix** Adhesive (see technical data sheet)

## T2Reflecta plate preparation

The aluminium surface of T2Reflecta must be clean, Level and dry. T2Reflecta plates are to be glued to the subfloor or fixed by screws.

Further more, the plates have to be free of dust, dirt, oil, grease and loose particles. The T2Red heating cable is to be laid in the grooves of the T2Reflecta plates.



---

## Usage Instruction

- Stir T2Reflecta-P-Fix Primer before use
- Apply the primer thinly with a flat wall brush, water brush, ceiling brush or short floor roller to achieve a uniform coat. Avoid forming pools.
- After allowing approx. 1-3 hours to dry, ceramic floors and natural stone floors can be laid using any\* flexible tile adhesive (\*in quality class C2 according to BS EN 12004 appropriate for floor heating)
- Clean tools in water immediately after use.

---

## Notes

All provided figures are approximate values and are subject to change depending on ambient conditions. Read and follow the product data sheets for all relevant RAYCHEM products. T2Reflecta-P-Fix Primer is not for use in areas permanently under water.

---

## Compatibility and the environment

- GISCODE D 1
- To Prevent accidents and safeguard health, please read and follow measures documented in the safety data sheet and product labelling.

Raychem is a registered trademark of Tyco Thermal Controls.

All of the above information, including illustrations, is believed to be reliable. Users however, should independently evaluate the suitability of each product for their application. Tyco Thermal Controls makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Thermal Controls only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Thermal Controls be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Thermal Controls Specifications are subject to change without notice. In addition Tyco Thermal Controls reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.

---

**tyco**  
*Thermal Controls*

For more information, contact your local representative.

[www.raychemfloorheating.com](http://www.raychemfloorheating.com)

**United Kingdom**  
Free phone 0800 96 90 13  
Free fax 0800 96 86 24  
salesUK@tycothermal.com

**Ireland**  
Free phone 1800 654 241  
Free fax 1800 654 240  
salesIE@tycothermal.com