

Floor heating T2QuickNet

Building materials product recommendation

for Finland, Sweden & Norway

Version: 03/2005

System - partner:



Electrical floor heating T2QuickNet - self-adhering mat

Applications: Private bathrooms, shower areas, kitchens and livingrooms

Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles
Top floor		Tiles	Marble + Natural stone*	Tiles
Working steps	Product type	CERESIT Technical support 0049 0211 - 7379- 401/405		
1. Apply a primer	Dispersion based primer	CT 17	CT 17	CN 94
2. Install electrical floor heating		Raychem T2QuickNet - self adhering -		
3. Level out unevenness (optional)	Self levelling material	CN 72 2- 15 mm	CN 72 2 - 15 mm	CN 73 flexibel CN 72 2 - 15 mm
4. Apply water barrier (optional)	Waterproofing material	CL 50 / 51	CL 50 / 51	CL 50 / 51 CF 41 / CL 50
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	Ceromit "Easy-Technologie" CM 18 / CM 17 CM 24 / CM 13	Ceromit CM 15 / CM 24	Ceromit "Easy-Technologie" CM 18 / CM 17 CM 24 / CM 13
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	CE 37 flexibel 2- 15 mm	CE 38 / CE 42	CE 37 flexibel 2- 15 mm
7. Apply rubberised grout between wall and floor	Silicone sealant	CS 24 SKM - Sanitär	CS 28 Marmorfuge	CS 25 SKM - Sanitär

*) for more detailed informations go in contact with supplier Ceresit

Tyco Thermal Controls N.V.
Staatsbaan 4A
3210 Lubbeek - Belgium

For Sweden - Tel.: +46 20-210100
For Norway - Tel.: +47 66-817990
www.raychemfloorheating.com

