

### Building materials product recommendation

for Finland, Sweden & Norway

Version: 04/2004

**System - partner:**



#### Electrical floor heating T2QuickNet - self-adhering mat

**Applications:** Private bathrooms, shower areas, kitchens and livingrooms

Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles
Top floor		Tiles	Marble + Natural stone*	Tiles
Working steps	Product type	<b>Optiroc Oy AB ( Deitermann) Finland</b> Technical support Tel.: + 358 / 10 / 44 22 00 <b>Byggprodukter A/S (Deitermann) Norway</b> Technical support Tel.: + 47 / 55 / 94 77 40 <b>Optiroc AB (Deitermann) Sweden</b> Technical support Tel.: + 46 / 40 / 6 71 27 70		
1. Apply a primer	Dispersion based primer	EUROLAN TG 2	EUROLAN TG 2	EUROLAN TG 5
<b>2. Install electrical floor heating</b>		<b>Raychem T2QuickNet - self adhering -</b>		
3. Level out unevenness (optional)	Self levelling material	Deitermann GM 10	Deitermann GM 10	Deitermann GM 40
4. Apply water barrier (optional)	Waterproofing material	Superflex 1 Superflex D1	Superflex 1 Superflex D1	Superflex 1 Superflex D1
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	Plastikol KM Flex Plastikol KM Flex+Fix Plastikol KMH Flex Deitermann KMH Flex+Fix	KM Flex+Fix weiss Plastikol K30	Plastikol KM Flex Plastikol KM Flex + Fix Plastikol KMH Flex Deitermann KMH Flex+Fix
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	CERINOL Flex	CERINOL FN CERINOL Flex	CERINOL Flex
7. Apply rubberised grout between wall and floor	Silicone sealant	Plastikol FDN Plastikol FDS	Plastikol FDX	Plastikol FDN Plastikol FDS

\*) for more detailed information please contact **Deitermann** direct

Tyco Thermal Controls N.V.  
Staatsbaan 4A  
3210 Lubbeek - Belgium

For Sweden - Tel.: +46 20-210100  
For Norway - Tel.: +47 66-817990  
www.raychemfloorheating.com

