

Building materials product recommendation

for Sweden & Norway

Version: 04/2004

System - partner:



Electrical floor heating T2QuickNet - self-adhering mat

Applications: Private bathrooms, shower areas, kitchens and livingrooms

Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles	
Top floor		Tiles	Marble + Natural stone*	Tiles	
Working steps	Product type	PCI Sverige(ing°ar i BKN AB); Phone: 0046 31-26 84 60 PCI Norge AS (Degussa Construction Chemicals Norge AS); Phone: 0047 22 90 19 70			
1. Apply a primer	Dispersion based primer	PCI-Gisogrund PCI-Gisofix	PCI-Gisogrund PCI-Gisofix	PCI-Gisogrund PCI-Gisofix	PCI-Gisogrund PCI-Gisofix
Raychem T2QuickNet - self adhering -					
2. Install electrical floor heating					
3. Level out unevenness (optional)	Self levelling material	PCI-Periplan	PCI-Periplan	PCI-Periplan	PCI-Periplan
4. Apply water barrier (optional)	Waterproofing material	PCI-Lastogum X	PCI-Lastogum X	PCI-Lastogum X	PCI-Lastogum X
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	PCI-Flexfix PCI-Polyflott	PCI-Carraflex PCI-Carraflott 7	PCI-Flexfix PCI-Polyflott	PCI-Flexfix PCI-Polyflott
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	PCI-Megafug	PCI-Megafug	PCI-Megafug	PCI-Megafug
7. Apply rubberised grout between wall and floor	Silicone sealant	PCI Silcoferm S	PCI Silcoferm S	PCI Silcoferm S	PCI Silcoferm S

*) for more detailed information please contact PCI direct

Tyco Thermal Controls N.V.
Staatsbaan 4A
3210 Lubbeek - Belgium

For Sweden - Tel.: +46 20-210100
For Norway - Tel.: +47 66-817990
www.raychemfloorheating.com

