

### Building materials product recommendation

For Sweden, Norway, Finland

Version: 04/2004

System - partner:



#### Electrical floor heating T2Red - self-regulating

**Applications:** Private bathrooms, shower areas, kitchens and living rooms

Sub floor		Cement screed, Anhydrite screed		timber floor board, particle board*		Old tiles
Top floor		Tiles	Marble+Natural stone*	Tiles		Tiles
<b>Working steps</b>	<b>Product type</b>	<b>Sweden - ARDEX-ARKI AB</b> e-Mail: ardex@ardex.se; Tel.: 08-556 315 50 <b>Norway - Ardex Skandinavia as</b> e-Mail: ardex@ardex.no; Telefon: 22 61 05 00 <b>Finland - ARDEX Oy</b> e-Mail: ardex@ardex.fi ; Telefon + 358 9 6869 140				
1. Apply a primer	Dispersion based primer	ARDEX P51	ARDEX P51	ARDEX P51		ARDEX P82
<b>2. Install electrical floor heating</b>		<b>Raychem T2Red - heating cable - self-regulating -</b>				
3. Level out unevenness	Self levelling surfacer	ARDEX S48	ARDEX S16 + ARDEX E 90	ARDEX S48		ARDEX S48
4. Apply water barrier (optional)	Waterproofing	ARDEX 8+9	ARDEX 8+9	ARDEX 8+9		ARDEX 8+9
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	ARDEX S48	ARDEX S16 + ARDEX E 90	ARDEX S48		ARDEX S48
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	ARDEX FL	ARDEX MG	ARDEX FL		ARDEX FL
7. Apply rubberised grout between wall and floor	Silicone sealant	ARDEX SE or ARDEX SN	ARDEX ST**	ARDEX SE or ARDEX SN		ARDEX SE or ARDEX SN

\*) for more detailed information please contact ARDEXdirect;

\*\*) Please see technical data sheet

Tyco Thermal Controls N.V.  
Staatsbaan 4A  
3210 Lubbeek - Belgium

Tel.: UK 0800 969013  
Fax.: UK 0800 968624  
www.raychemfloorheating.com



**tyco**  
Flow Control

**Tyco Thermal Controls**