

# Floor heating T2Red

## Building materials product recommendation

For Sweden, Norway & Finland

Version: 03/2005

System - partner:



### Electrical floor heating T2Red - self-regulating

**Applications:** Private bathrooms, shower areas, kitchen and living rooms

Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles
Top floor		Tiles	Marble+Natural stone*	Tiles
<b>Working steps</b>	<b>Product type</b>	<b>CERESIT Technical Support 0049 (0) 211 - 7379- 400/405</b>		
<b>1. Apply a primer</b>	Dispersion based primer	CT 17	CT 17	CN 94
<b>2. Install electrical floor heating</b>		<b>Raychem T2Red - heating cable - self regulating -</b>		
<b>3. Level out unevenness</b>	Self levelling surfacer	CN 72 2- 15 mm	CN 72 2 - 15 mm	CN 73 flexibel CN 72 2 - 15 mm
<b>4. Apply water barrier (optional)</b>	Waterproofing	CL 50 / 51	CL 50 / 51	CL 50 / 51 CL 50
<b>5. Lay ceramic tiles</b>	Adhesive, improved with synthetics, classified as C2 according to EN 12004	<b>Ceromit "Easy-Technologie" CM 18 / CM 17 CM 24 / CM 13</b>	<b>Ceromit CM 15 / CM 24</b>	<b>Ceromit "Easy-Technologie" CM 18 / CM 17 CM 24 / CM 13</b>
<b>6. Apply grout between ceramic tiles</b>	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	CE 37 I 2- 15 mm	CE 38 / CE 42	CE 37 2- 15 mm CE 37 2- 15 mm
<b>7. Apply rubberised grout between wall and floor</b>	Silicone sealant	CS 24 SKM - Sanitär	CS 28 Marmorfuge	CS 25 - Sanitär SKM CS 25 SKM - Sanitär

\*) for more detailed informations go in contact with supplier CERESIT



Tyco Thermal Controls N.V.  
Staatsbaan 4A  
3210 Lubbeek - Belgium

For Sweden - Tel.: +46 20-210100  
For Norway - Tel.: +47 66-817990  
www.raychemfloorheating.com