

Building materials product recommendation

For Sweden, Norway & Finland

Version: 04/2004

System - partner:

DEITERMANN

Qualität - Sicherheit - Service



Electrical floor heating T2Red - self-regulating

Applications: Private bathrooms, shower areas, kitchen and living rooms

Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles
Top floor		Tiles	Marble+Natural stone*	Tiles
Working steps	Product type	Optiroc Oy AB (Deitermann) Finland Technical support Tel.: + 358 / 10 / 44 22 00 Byggprodukter A/S (Deitermann) Norway Technical support Tel.: + 47 / 55 / 94 77 40 Optiroc AB (Deitermann) Sweden Technical support Tel.: + 46 / 40 / 6 71 27 70		
1. Apply a primer	Dispersion based primer	EUROLAN TG 2	EUROLAN TG 2	EUROLAN TG 5
2. Install electrical floor heating		Raychem T2Red - heating cable - self regulating -		
3. Level out unevenness	Self levelling surfacer	Deitermann GM 40	Deitermann GM 40	Deitermann GM 40
4. Apply water barrier (optional)	Waterproofing	Superflex 1 / Superflex D1	Superflex 1 / Superflex D1	Superflex 1 / Superflex D1
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	Plastikol KM Flex Plastikol KM Flex+Fix Plastikol KMH Flex Deitermann KMH Flex+Fix	KM Flex+Fix weiss/ Plastikol K 30	PLASTIKOL KM Flex / Plastikol KM Flex + Fix Plastikol KMH Flex / Deitermann KMH Flex + Fix
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	CERINOL Flex	CERINOL FN / CERINOL Flex	CERINOL Flex
7. Apply rubberised grout between wall and floor	Silicone sealant	PLASTIKOL FDN / Plastikol FDS	PLASTIKOL FDX	PLASTIKOL FDN / PLASTIKOL FDS

*) for more detailed information please contact **Deitermann** direct



tyco
Flow Control

Tyco Thermal Controls

Tyco Thermal Controls N.V.
Staatsbaan 4A
3210 Lubbeek - Belgium

For Sweden - Tel.: +46 20-210100
For Norway - Tel.: +47 66-817990
www.raychemfloorheating.com