

Building materials product recommendation

For Sweden, Norway & Finland
Version: 04/2004

System - partner:



Electrical floor heating T2Red - self-regulating

Applications: Private bathrooms, shower areas, kitchen and living rooms

Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles
Top floor		Tiles	Marble+Natural stone*	Tiles
Working steps	Product type	Rescon Mapei AS Norway - Technical support: phone: +47 62 97 20 00 ; Rescon Mapei OY Finland - Technical support phone: + 358 986 78 900; Rescon Mapei AB Sweden - Technical support: phone: 08 660 71 35 ;		
1. Apply a primer	Dispersion based primer	Primer G	Primer G	Bonding primer Mapeprime 1K+Quarzsand (Körnung 0,7-1,2mm)
2. Install electrical floor heating		Raychem T2Red - heating cable - self-regulating -		
3. Level out unevenness	Self levelling surfacer	Mapestone 1	Mapestone 1	Mapestone 1
4. Apply water barrier (optional)	Waterproofing	Mapelastic + DHT Dichtsystem	Mapelastic + DHT Dichtsystem	Keraquick+Latex Plus, Mapetexvlies, Mapelastic + DHT Dichtsystem
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	Keraflex S1 Keraflex Maxi Keraquick Mapestone 1	Granirapid Keraquick Mapestone 1 Keraquick+Latex Plus	Keraquick+Latex Plus Keraflex S1 Keraflex Maxi Keraquick Mapestone 1
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	Ultracolor	Ultracolor	Ultracolor
7. Apply rubberised grout between wall and floor	Silicone sealant	Mapesil AC	Mapesil LM	Mapesil AC

*) for more detailed information please contact **Mapei** direct

