

# Floor heating T2Reflecta + T2Red

## Building materials product recommendation

For Sweden, Finland & Norway

Version: 04/2004

System - partner:



Electrical floor heating T2Reflecta + T2Red - FIX System /self-regulating

Applications: Private bathrooms, kitchen and living rooms etc.

Sub floor		Cement screed, Anhydrite screed		timber floor board, particle board*		Old tiles		asphalt screed*
Top floor		Tiles	Marble+Natural stone*	Tiles		Tiles		Tiles
<b>Working steps</b>	<b>Product type</b>	<b>Optiroc Oy AB ( Deitermann) Finland</b> Technical support Tel.: + 358 / 10 / 44 22 00 <b>Byggprodukter A/S (Deitermann) Norway</b> Technical support Tel.: + 47 / 55 / 94 77 40 <b>Optiroc AB (Deitermann) Sweden</b> Technical support Tel.: + 46 / 40 / 6 71 27 70						
1. Apply a primer	Dispersion based primer	Eurolan TG 2	Eurolan TG 5	Eurolan TG 5	Eurolan TG 5	Eurolan TG 5	Eurolan TG 5	Eurolan TG 5
2. Level out unevenness (optional)	Self levelling material	Deitermann GM 10	Deitermann GM 10	Deitermann GM 40	Deitermann GM 40	Deitermann GM 10	Deitermann GM 10	Deitermann GM 10
3. Fixation T2Reflecta plates	Adhesive, improved with synthetics, classified as C2F according to EN 12004	<b>T2Reflecta A-Fix**</b>	<b>T2Reflecta A-Fix**</b>	<b>T2Reflecta A-Fix**</b>	<b>T2Reflecta A-Fix**</b>	<b>T2Reflecta A-Fix**</b>	<b>T2Reflecta A-Fix**</b>	<b>T2Reflecta A-Fix**</b>
<b>4. Install electrical floor heating Raychem T2Reflecta + T2Red - self regulating -</b>								
5. Apply a primer	Dispersion based primer	<b>T2Reflecta P-Fix**</b>	<b>T2Reflecta P-Fix**</b>	<b>T2Reflecta P-Fix**</b>	<b>T2Reflecta P-Fix**</b>	<b>T2Reflecta P-Fix**</b>	<b>T2Reflecta P-Fix**</b>	<b>T2Reflecta P-Fix**</b>
6. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2F according to EN 12004	Plastikol KM Flex Plastikol KM Flex+Fix Plastikol KMH Flex Deitermann KMH Flex+Fix	Plastikol KM Flex + Fix weiss	Plastikol KM Flex Plastikol KM Flex+Fix Plastikol KMH Flex Deitermann KMH Flex+Fix	Plastikol KM Flex Plastikol KM Flex+Fix Plastikol KMH Flex Deitermann KMH Flex+Fix	Plastikol KM Flex Plastikol KM Flex+Fix Plastikol KMH Flex Deitermann KMH Flex+Fix	Plastikol KM Flex Plastikol KM Flex+Fix Plastikol KMH Flex Deitermann KMH Flex+Fix	Plastikol KM Flex Plastikol KM Flex+Fix Plastikol KMH Flex Deitermann KMH Flex+Fix
7. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	Cerinol Flex	Cerinol FN	Cerinol Flex	Cerinol Flex	Cerinol Flex	Cerinol Flex	Cerinol Flex
8. Apply rubberised grout between wall and floor	Silicone sealant	Plastikol FDN Plastikol FDS	Plastikol FDN Plastikol FDS	Plastikol FDN Plastikol FDS	Plastikol FDN Plastikol FDS	Plastikol FDN Plastikol FDS	Plastikol FDN Plastikol FDS	Plastikol FDN Plastikol FDS

\*) for more detailed information please contact **Deitermann** direct  
 \*\*) to obtain the product data sheet please contact **Tyco Thermal Controls**

Tyco Thermal Controls N.V.  
 Staatsbaan 4A  
 3210 Lubbeek - Belgium

For Sweden - Tel.: +46 20-210100  
 For Norway - Tel.: +47 66-817990  
 www.raychemfloorheating.com

