

Building materials product recommendation


Version: 04/2009

System - partner:



Electrical floor heating T2ISOLECTA+ T2Blue 10

Application: Private bathrooms, kitchen and living rooms etc.



Sub floor		Cement screed		timber floor board, particle board*
Top floor		Tiles	Marble+Natural stone*	Tiles
Working steps		AKZO NOBEL Casco Technical support Tel.: 0049 (0) 2363 399 - 0 (Region: Scandinavia - S, N, FIN)		
Product group				
1. Apply a primer	Dispersion based primer	Casco Golvprimer	Casco Golvprimer	*)
2. Level out unevennesses (optional)	Self levelling surfacer	Cascoplan Thermoplan	Cascoplan Thermoplan	Cascoplan Thermoplan
3. Fixation Isolecta boards	Adhesive, improved with synthetics, classified as C2F according to EN 12004	CASCO Multifix Rapid	CASCO Multifix Rapid	CASCO Multifix Rapid + mechanical fixing
4. Install electrical floor heating T2Blue-10 heating cable				
5. Embedding in filler material	Self levelling surfacer	Cascoplan Thermoplan	Cascoplan Thermoplan	Cascoplan Thermoplan
6. Apply water proofing (optional)	Waterproofing	Casco Golvprimer/ Casco Augastop	Casco Golvprimer/ Casco Augastop	Casco Golvprimer/ Casco Augastop
7. Fixation ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	Casco FloorFlex	Casco Multifix white	Casco FloorFlex
8. Filling grouts between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	Casco Flexo	Casco Flexo	Casco Flexo
9. Filling elastic grouts between wall and floor	Silicone sealant	Casco sealing	Casco sealing	Casco sealing

*) for more detailed informations go in contact with supplier **Casco**

) for getting the product data sheet go in contact with **Tyco Thermal Controls



Tyco Thermal Controls N.V.
Romeinse straat 14
3001 Leuven - Belgium