



### Electrical floor heating T2ISOLECTA+ T2Blue 10

**Application:** Private bathrooms, kitchen and living rooms etc.



Sub floor		Cement screed		timber floor board, particle board*
Top floor		Tiles	Marble+Natural stone*	Tiles
<b>Working steps</b>		<b>MAPEI</b>		
		Technical support Tel.: 0049 (0) 20 41 / 20 86 6 ( Region - Scandinavia S, N, FIN )		
<b>1. Apply a primer</b>	Dispersion based primer	Primer G	Primer G	Primer S
<b>2. Level out unevennesses (optional)</b>	Self levelling surfacer	Ultraplan Ultraplan Maxi	Ultraplan Ultraplan Maxi	Fiberplan
<b>3. Fixation Isolecta boards</b>	Adhesive, improved with synthetics, classified as C2F according to EN 12004	KERAQUICK , ADESILEX P4	KERAQUICK , ADESILEX P4	KERAQUICK , ADESILEX P4
<b>4. Install electrical floor heating T2Blue-10 heating cable</b>				
<b>5. Embedding in filler material</b>	Self levelling surfacer	Ultraplan Ultraplan Maxi	Ultraplan Ultraplan Maxi	Fiberplan
<b>6. Apply water proofing (optional)</b>	Waterproofing	Mapelastc + DHT Dichtsystem	Mapelastc + DHT Dichtsystem	Keraquick + Latex plus Mapetexvlies Mapelastc+DHT Dichtsystem
<b>7. Fixation ceramic tiles</b>	Adhesive, improved with synthetics, classified as C2 according to EN 12004	Keraflex S1 Keraquick Mapestone1 Keraflex Maxi	Granirapid Keraquick Mapestone 1 Keraquick+Latex plus	Keraquick + Latex plus
<b>8. Filling grouts between ceramic tiles</b>	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	Ultracolor	Ultracolor	Ultracolor
<b>9. Filling elastic grouts between wall and floor</b>	Silicone sealant	Mapesil AC	Mapesil LN	Mapesil AC

\*) for more detailed informations go in contact with supplier **MAPEI**

\*\*) for getting the product data sheet go in contact with **Tyco Thermal Controls**



**tyco**

Flow Control

**Tyco Thermal Controls**