

### Building materials product recommendation

For Sweden, Norway, Finland


Version: 04/2004

**System - partner:**



#### Electrical floor heating T2QuickNet - self-adhering mat

**Applications:** Private bathrooms, shower areas, kitchens and living rooms



Sub floor		Cement screed, Anhydrite screed		timber floor board, particle board*		Old tiles	
Top floor		Tiles	Marble + Natural stone*	Tiles		Tiles	
Working steps	Product type	<b>Sweden - ARDEX-ARKI AB</b> e-Mail: ardex@ardex.se; Tel.: 08-556 315 50 <b>Norway - Ardex Skandinavia as</b> e-Mail: ardex@ardex.no; Telefon: 22 61 05 00 <b>Finland - ARDEX Oy</b> e-Mail: ardex@ardex.fi ; Telefon + 358 9 6869 140					
1. Apply a primer	Dispersion based primer	ARDEX P51	ARDEX P51	ARDEX P51	ARDEX P51	ARDEX P51	ARDEX P82
<b>2. Install electrical floor heating</b>		<b>Raychem T2QuickNet - self adhering -</b>					
3. Level out unevenness	Self levelling material	ARDEX S48	ARDEX S16 + ARDEX E90	ARDEX S48	ARDEX S48	ARDEX S48	ARDEX S48
4. Apply water barrier (optional)	Waterproofing material	ARDEX 8+9	ARDEX 8+9	ARDEX 8+9	ARDEX 8+9	ARDEX 8+9	ARDEX 8+9
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	ARDEX S48	ARDEX S16 + ARDEX E90	ARDEX S48	ARDEX S48	ARDEX S48	ARDEX S48
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	ARDEX FL	ARDEX MG	ARDEX FL	ARDEX FL	ARDEX FL	ARDEX FL
7. Apply rubberised grout between wall and floor	Silicone sealant	ARDEX SE or ADREX SN	ARDEX ST**	ARDEX SE or ARDEX SN	ARDEX SE or ARDEX SN	ARDEX SE or ARDEX SN	ARDEX SE or ARDEX SN

\*) for more detailed information please contact **ARDEX** direct

Tyco Thermal Controls N.V.  
Staatsbaan 4A  
3210 Lubbeek - Belgium

Tel.: UK 0800 969013  
Fax.: UK 0800 968624  
www.raychemfloorheating.com



**tyco**

Flow Control

Tyco Thermal Controls