

### Building materials product recommendation

For Sweden & Norway

Version: 04/2004

System - partner:



#### Electrical floor heating T2Red - self-regulating

**Applications:** Private bathrooms, shower areas, kitchen and living rooms

Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles
Top floor		Tiles	Marble+Natural stone*	Tiles
<b>Working steps</b>	<b>Product type</b>	<b>Akzo Nobel Deco International AB/Casco</b> - Sweden Technical support Tel. 08 - 7434000 <b>Akzo Nobel Decorative AS /Casco</b> - Norway Technical support Tel. 66 81 94 00		
1. Apply a primer	Dispersion based primer	Casco Golvprimer	Casco Golvprimer	Schönox PX
<b>2. Install electrical floor heating</b>		<b>Raychem T2Red - heating cable - self-regulating -</b>		
3. Level out unevenness	Self levelling surfacer	Cascoplan Thermoplan	Cascoplan Thermoplan	Cascoplan Thermoplan
4. Apply water barrier (optional)	Waterproofing	Casco Golvprimer/ Casco Aquastop	Casco Golvprimer/ Casco Aquastop	Casco Golvprimer/ Casco Aquastop
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	Casco FloorFlex	Casco Multifix white	Casco FloorFlex
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	Casco Flexo	Casco Flexo	Casco Flexo
7. Apply rubberised grout between wall and floor	Silicone sealant	Casco sealing	Casco sealing	Casco sealing

\*) for more detailed information please contact Casco direct

