

Building materials product recommendation


For United Kingdom
Version: 04/2004

System - partner:



Electrical floor heating T2QuickNet - self-adhering mat

Applications: Private bathrooms, shower areas, kitchens and living rooms



Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles
Top floor		Tiles	Marble + Natural stone*	Tiles
Working steps	Product type	ARDEX UK Limited E-mail: info@ardex.co.uk Technical Services Tel: +44 (0)1440 714939 (Region: Western Europe - UK)		
1. Apply a primer	Dispersion based primer	ARDEX P51	ARDEX P51	ARDEX P51
2. Install electrical floor heating		Raychem T2QuickNet - self adhering -		
3. Level out unevenness	Self levelling material	ARDEX S48	ARDEX S16 + ARDEX E90	ARDEX S48
4. Apply water barrier (optional)	Waterproofing material	ARDEX 8+9	ARDEX 8+9	ARDEX 8+9
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	ARDEX S48	ARDEX S16 + ARDEX E90	ARDEX S48
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	ARDEX FL	ARDEX MG	ARDEX FL
7. Apply rubberised grout between wall and floor	Silicone sealant	ARDEX SE or ADREX SN	ARDEX ST**	ARDEX SE or ARDEX SN

*) for more detailed information please contact **ARDEX** direct

Tyco Thermal Controls N.V.
Staatsbaan 4A
3210 Lubbeek - Belgium

Tel.: UK 0800 969013
Fax.: UK 0800 968624
www.raychemfloorheating.com



tyco
Flow Control

Tyco Thermal Controls