

Building materials product recommendation

For France, Uk and Italy

Version: 04/2004

System - partner:



Electrical floor heating T2QuickNet - self-adhering mat

Applications: Private bathrooms, shower areas, kitchens and livingrooms



Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles
Top floor		Tiles	Marble + Natural stone*	Tiles
Working steps	Product type	Mapei (UK) Limited Technical support phone.: 0121 508 6970 (Region: Western Europe UK) MAPEI S.p.A. Technical support phone: +39 02 37673.1 (Region: Western Europe France, Italy)		
1. Apply a primer	Dispersion based primer	Primer G	Primer G	Bonding primer Mapeprim 1 K + Quarzsand
2. Install electrical floor heating		Raychem T2QuickNet - self adhering -		
3. Level out unevenness (optional)	Self levelling material	Ultraplan Ultraplan Maxi	Ultraplan Ultraplan Maxi	Fiberplan Ultraplan Ultraplan Maxi
4. Apply water barrier (optional)	Waterproofing material	Mapelastic + DHT Dichtsystem	Mapelastic + DHT Dichtsystem	Keraquick + Latex plus Mapetexvlies Mapelastic+DHT Dichtsystem Mapelastic + DHT Dichtsystem
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2 according to EN 12004	Keraflex S1 Keraquick Mapestone1 Keraflex Maxi	Granirapid Keraquick Mapestone 1 Keraquick+Latex plus	Keraquick + Latex plus Keraflex S1 Keraquick Mapestone1
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	Ultracolor	Ultracolor	Ultracolor Ultracolor
7. Apply rubberised grout between wall and floor	Silicone sealant	Mapesil AC	Mapesil LN	Mapesil AC Mapesil AC

*) for more detailed information please contact **Mapeidirect**

Tyco Thermal Controls N.V.
Staatsbaan 4A
3210 Lubbeek - Belgium

Tel.: F 0800 906045
Tel.: UK 0800 969013
www.raychemfloorheating.com

