

### Building materials product recommendation

For UK , France and Italy

Version: 04/2004

**System - partner:**



#### Electrical floor heating T2Red - self-regulating

**Applications:** Private bathrooms, shower areas, kitchens and living rooms

Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles
Top floor		Tiles	Marble+Natural stone*	Tiles
<b>Working steps</b>	<b>Product type</b>	<b>Mapei (UK)</b> Limited Technical support phone.: 0121 508 6970 (Region: Western Europe UK) <b>MAPEI S.p.A.</b> Technical support phone: +39 02 37673.1 (Region: Western Europe France, Italy)		
<b>1. Apply a primer</b>	Dispersion based primer	Primer G	Primer G	Bonding primer Mapeprime 1K+Quarzsand (Körnung 0,7-1,2mm)
<b>2. Install electrical floor heating</b>		<b>Raychem T2Red - heating cable - self-regulating -</b>		
<b>3. Level out unevenness</b>	Self levelling surfacer	Mapestone 1	Mapestone 1	Mapestone 1
<b>4. Apply water barrier (optional)</b>	Waterproofing	Mapelastic + DHT Dichtsystem	Mapelastic + DHT Dichtsystem	Keraquick+Latex Plus, Mapetexvlies, Mapelastic + DHT Dichtsystem
<b>5. Lay ceramic tiles</b>	Adhesive, improved with synthetics, classified as C2 according to EN 12004	Keraflex S1 Keraflex Maxi Keraquick Mapestone 1	Granirapid Keraquick Mapestone 1 Keraquick+Latex Plus	Keraquick+Latex Plus
<b>6. Apply grout between ceramic tiles</b>	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	Ultracolor	Ultracolor	Ultracolor
<b>7. Apply rubberised grout between wall and floor</b>	Silicone sealant	Mapesil AC	Mapesil LM	Mapesil AC

\*) for more detailed information please contact **Mapei** direct

