

### Building materials product recommendation

For United Kingdom

Version: 04/2004

System - partner:



#### Electrical floor heating T2Red - self-regulating

**Applications:** Private bathrooms, shower areas, kitchens and living rooms

Sub floor		Cement screed, Anhydrite screed		timber floor board, particle board*		Old tiles
Top floor		Tiles	Marble+Natural stone*	Tiles		Tiles
<b>Working steps</b>	<b>Product type</b>	<b>PCI Construction Systems Ltd.</b> Technical support: phone: 0044 191 428 1717 (Region: Western Europe - UK)				
<b>1. Apply a primer</b>	Dispersion based primer	PCI Primer G PCI-Gisofix NT	PCI Primer G PCI-Gisofix NT	PCI Primer G PCI-Gisofix NT		PCI Primer G PCI-Gisofix NT
<b>2. Install electrical floor heating</b>		<b>Raychem T2Red - heating cable - self-regulating -</b>				
<b>3. Level out unevenness</b>	Self levelling surfacer	PCI-Periplan	PCI-Periplan	PCI-Periplan		PCI-Periplan
<b>4. Apply water barrier (optional)</b>	Waterproofing	PCI-Lastogum X	PCI-Lastogum X	PCI-Lastogum X		PCI-Lastogum X
<b>5. Lay ceramic tiles</b>	Adhesive, improved with synthetics, classified as C2 according to EN 12004	PCI-Tilefast 6 Flex	PCI-Carraflex PCI-Carraflott	PCI-Tilefast 6 Flex		PCI-Tilefast 6 Flex
<b>6. Apply grout between ceramic tiles</b>	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	PCI-Groutfast 20 Rapidflex	PCI-Groutfast 20 Rapidflex	PCI-Groutfast 20 Rapidflex		PCI-Groutfast 20 Rapidflex
<b>7. Apply rubberised grout between wall and floor</b>	Silicone sealant	PCI Silcoferm S	PCI Silcoferm S	PCI Silcoferm S		PCI Silcoferm S

\*) for more detailed information please contact **PCI**direct

Tyco Thermal Controls N.V.  
Staatsbaan 4A  
3210 Lubbeek - Belgium

Tel.: UK 0800 969013  
Fax.: UK 0800 968624  
[www.raychemfloorheating.com](http://www.raychemfloorheating.com)

