


Floor heating T2Reflecta + T2Red

Building materials product recommendation

For UK and Italy
Version: 05/2005

System - partner:



Electrical floor heating T2Reflecta + T2Red - self-regulating

Applications: Private bathrooms, kitchen and living rooms etc.

Sub floor		Cement screed, Anhydrite screed	timber floor board, particle board*	Old tiles	asphalt screed*
Top floor		Tiles	Marble+Natural stone*	Tiles	Tiles
Working steps	Product type	Ceresit Technical support			
		(0)211 - 7379- 400/405			
1. Apply a primer	Dispersion based primer	CT 17	CT 17	CN 94	CN 94
2. Level out unevenness (optional)	Self levelling material	CN 72 2- 15 mm	CN 72 2- 15 mm	CN 73	CN 73
3. Fixation T2Reflecta plates	Adhesive, improved with synthetics, classified as C2F according to EN 12004	T2Reflecta Adhesive S* *	T2Reflecta Adhesive S**	T2Reflecta Adhesive S**	T2Reflecta Adhesive S* *
4. Install electrical floor heating		Raychem T2Reflecta + T2Red - self regulating -			
5. Lay ceramic tiles	Adhesive, improved with synthetics, classified as C2F according to EN 12004	T2Reflecta Adhesive S* *	T2Reflecta Adhesive S**	T2Reflecta Adhesive S**	T2Reflecta Adhesive S* *
6. Apply grout between ceramic tiles	Grout filler improved with synthetics, classified as CG2 according to EN 13888 for ceramic tiles	CE 37 flexibel 2- 15 mm	CE 38 / CE 42	CE 37 2- 15 mm	CE 37 flexibel 2- 15 mm
7. Apply rubberised grout between wall and floor	Silicone sealant	CS 24 SKM - Sanitär	CS 28 Marmorfuge	CS 25 SKM - Sanitär	CS 25 SKM - Sanitär

*) for more detailed informations go in contact with supplier Ceresit **) Product information from Tyco Thermal Controls



Tyco Thermal Controls N.V.
Staatsbaan 4A
3210 Lubbeek - Belgium

Tel.: UK 0800 969013
www.raychemfloorheating.com